

`CURLOPT_CHUNK_LENGTH_PENALTY_SIZE(3)` setopt(3) `CURLOPT_CHUNK_LENGTH_PENALTY_SIZE(3)`

NAME

`CURLOPT_CHUNK_LENGTH_PENALTY_SIZE` – chunk length threshold for pipelining

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLMcode curl_multi_setopt(CURLM *handle, CURLOPT_CHUNK_LENGTH_PENALTY_SIZE,  
long size);
```

DESCRIPTION

Pass a long with a **size** in bytes. If a pipelined connection is currently processing a chunked (Transfer-encoding: chunked) request with a current chunk length larger than `CURLOPT_CHUNK_LENGTH_PENALTY_SIZE(3)`, that pipeline will not be considered for additional requests, even if it is shorter than `CURLOPT_MAX_PIPELINE_LENGTH(3)`.

DEFAULT

The default value is 0, which means that the penalization is inactive.

PROTOCOLS

HTTP(S)

EXAMPLE

TODO

AVAILABILITY

Added in 7.30.0

RETURN VALUE

Returns `CURLM_OK` if the option is supported, and `CURLM_UNKNOWN_OPTION` if not.

SEE ALSO

`CURLOPT_PIPELINING(3)`, `CURLOPT_CONTENT_LENGTH_PENALTY_SIZE(3)`, `CURLOPT_MAX_PIPELINE_LENGTH(3)`,