

CURLOPT\_FNMATCH\_FUNCTION(3) curl\_easy\_setopt options CURLOPT\_FNMATCH\_FUNCTION(3)

## NAME

CURLOPT\_FNMATCH\_FUNCTION – wildcard matching function callback

## SYNOPSIS

```
#include <curl/curl.h>
```

```
int fnmatch_callback(void *ptr,  
                    const char *pattern,  
                    const char *string);
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_FNMATCH_FUNCTION,  
                          fnmatch_callback);
```

## DESCRIPTION

Pass a pointer to your callback function, which should match the prototype shown above.

This callback is used for wildcard matching.

Return *CURL\_FNMATCHFUNC\_MATCH* if pattern matches the string, *CURL\_FNMATCHFUNC\_NOMATCH* if not or *CURL\_FNMATCHFUNC\_FAIL* if an error occurred.

## DEFAULT

NULL == an internal function for wildcard matching.

## PROTOCOLS

FTP

## EXAMPLE

TODO

## AVAILABILITY

Added in 7.21.0

## RETURN VALUE

Returns CURLE\_OK if the option is supported, and CURLE\_UNKNOWN\_OPTION if not.

## SEE ALSO

CURLOPT\_FNMATCH\_DATA(3), CURLOPT\_DEBUGFUNCTION(3),