

NAME

CURLOPT_FTPSSLAUTH – set order in which to attempt TLS vs SSL when using FTP

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_FTPSSLAUTH, long order);
```

DESCRIPTION

Pass a long using one of the values from below, to alter how libcurl issues "AUTH TLS" or "AUTH SSL" when FTP over SSL is activated. This is only interesting if *CURLOPT_USE_SSL(3)* is also set.

Possible *order* values:

CURLFTPAUTH_DEFAULT

Allow libcurl to decide.

CURLFTPAUTH_SSL

Try "AUTH SSL" first, and only if that fails try "AUTH TLS".

CURLFTPAUTH_TLS

Try "AUTH TLS" first, and only if that fails try "AUTH SSL".

DEFAULT

CURLFTPAUTH_DEFAULT

PROTOCOLS

FTP

EXAMPLE

TODO

AVAILABILITY

Added in 7.12.2

RETURN VALUE

Returns CURLE_OK if the option is supported, and CURLE_UNKNOWN_OPTION if not.

SEE ALSO

CURLOPT_USE_SSL(3), *CURLOPT_FTP_SSL_CCC(3)*,