

CURLOPT\_FTP\_RESPONSE\_TIMEOUT(3)curl\_easy\_setopt optionsCURLOPT\_FTP\_RESPONSE\_TIMEOUT(3)

## NAME

CURLOPT\_FTP\_RESPONSE\_TIMEOUT – time allowed to wait for FTP response

## SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_FTP_RESPONSE_TIMEOUT, long timeout);
```

## DESCRIPTION

Pass a long. Causes libcurl to set a *timeout* period (in seconds) on the amount of time that the server is allowed to take in order to send a response message for a command before the session is considered dead. While libcurl is waiting for a response, this value overrides *CURLOPT\_TIMEOUT(3)*. It is recommended that if used in conjunction with *CURLOPT\_TIMEOUT(3)*, you set *CURLOPT\_FTP\_RESPONSE\_TIMEOUT(3)* to a value smaller than *CURLOPT\_TIMEOUT(3)*.

## DEFAULT

None

## PROTOCOLS

FTP

## EXAMPLE

TODO

## AVAILABILITY

Added in 7.10.8

## RETURN VALUE

Returns CURLE\_OK if FTP is supported, and CURLE\_UNKNOWN\_OPTION if not.

## SEE ALSO

CURLOPT\_TIMEOUT(3), CURLOPT\_CONNECTTIMEOUT(3), CUR-  
LOPT\_LOW\_SPEED\_LIMIT(3),