

NAME

CURLOPT_FTP_RESPONSE_TIMEOUT – time allowed to wait for FTP response

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_FTP_RESPONSE_TIMEOUT, long timeout);
```

DESCRIPTION

Pass a long. Causes libcurl to set a *timeout* period (in seconds) on the amount of time that the server is allowed to take in order to send a response message for a command before the session is considered dead. While libcurl is waiting for a response, this value overrides *CURLOPT_TIMEOUT(3)*. It is recommended that if used in conjunction with *CURLOPT_TIMEOUT(3)*, you set *CURLOPT_FTP_RESPONSE_TIMEOUT(3)* to a value smaller than *CURLOPT_TIMEOUT(3)*.

DEFAULT

None

PROTOCOLS

FTP

EXAMPLE

TODO

AVAILABILITY

Added in 7.10.8

RETURN VALUE

Returns CURLE_OK if FTP is supported, and CURLE_UNKNOWN_OPTION if not.

SEE ALSO

[CURLOPT_TIMEOUT\(3\)](#),
[LOPT_LOW_SPEED_LIMIT\(3\)](#),

[CURLOPT_CONNECTTIMEOUT\(3\)](#),

CUR-