

**NAME**

CURLOPT\_LOGIN\_OPTIONS – set login options

**SYNOPSIS**

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_LOGIN_OPTIONS, char *options);
```

**DESCRIPTION**

Pass a char \* as parameter, which should be pointing to the zero terminated *options* string to use for the transfer.

For more information about the login options please see RFC2384, RFC5092 and IETF draft draft-earhart-url-smtp-00.txt

*CURLOPT\_LOGIN\_OPTIONS(3)* can be used to set protocol specific login options, such as the preferred authentication mechanism via "AUTH=NTLM" or "AUTH=\*", and should be used in conjunction with the *CURLOPT\_USERNAME(3)* option.

**DEFAULT**

NULL

**PROTOCOLS**

Only IMAP, POP3 and SMTP support login options.

**EXAMPLE**

TODO

**AVAILABILITY**

Added in 7.34.0

**RETURN VALUE**

Returns CURLE\_OK if the option is supported, CURLE\_UNKNOWN\_OPTION if not, or CURLE\_OUT\_OF\_MEMORY if there was insufficient heap space.

**SEE ALSO**

*CURLOPT\_USERNAME(3)*, *CURLOPT\_PASSWORD(3)*,