

**NAME**

CURLOPT\_STREAM\_DEPENDS\_E – set stream this transfer depends on exclusively

**SYNOPSIS**

#include <curl/curl.h>

CURLcode curl\_easy\_setopt(CURL \*handle, CURLOPT\_STREAM\_DEPENDS\_E, CURL \*dephandle);

**DESCRIPTION**

Pass a CURL \* pointer in *dephandle* to identify the stream within the same connection that this stream is depending upon exclusively. That means it depends on it and sets the Exclusive bit.

The spec says "Including a dependency expresses a preference to allocate resources to the identified stream rather than to the dependent stream."

Setting a dependency with the exclusive flag for a reprioritized stream causes all the dependencies of the new parent stream to become dependent on the reprioritized stream.

This option can be set during transfer.

*dephandle* must not be the same as *handle*, that will cause this function to return an error. It must be another easy handle, and it also needs to be a handle of a transfer that will be sent over the same HTTP/2 connection for this option to have an actual effect.

**DEFAULT**

NULL

**PROTOCOLS**

HTTP/2

**EXAMPLE**

TODO

**AVAILABILITY**

Added in 7.46.0

**RETURN VALUE**

Returns CURLE\_OK if the option is supported, and CURLE\_UNKNOWN\_OPTION if not.

**SEE ALSO**

CURLOPT\_STREAM\_WEIGHT(3), CURLOPT\_STREAM\_DEPENDS(3),