



Tizen Content Screening Plug-in API Specification

Document version 1.1.3

Copyright (c) 2014, McAfee, Inc.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of McAfee, Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Document Information

Document Details

Revision	1.1.3
Author	MMS Development Team

Revision Information

Revision	Revision Date	Author	Details
1.0.0	11/13/2012	MMS Development Team	Created.
1.0.1	01/26/2013	MMS Development Team	Add license.
1.1.0	03/28/2014	MMS Development Team	Add details for TCSPGetVersion API.
1.1.1	06/24/2014	MMS Development Team	Updated document for scan cancel feature and TCSPGetInfo API.
1.1.2	07/07/2014	MMS Development Team	Update TCSGetInfo API, specify the returned string is well-formed XML string with character encoding in UTF-8.
1.1.3	07/30/2014	MMS Development Team	Fix backward compatible issue for scan API.

Contents

Terms, Abbreviations, Definitions, Conventions	5
Overview	6
Library	8
Initialize Functions	8
Get Version Function.....	8
Get Info Function.....	9
Scan Functions.....	9
Support Function.....	12
TCSScanParam.....	12
TCSScanResult	16
TCSDetected	16
Data Type	17
Action Type	18
CallBack Reason.....	18
Error Code.....	18
Call Sequence	20

Terms, Abbreviations, Definitions, Conventions

Items	Description
SDK	Software Development Kit
API	Application Programming Interface
Content Screening	Screening content for security consideration
Module	Program, service or any execution entity in the Tizen platform
Application	Executable provided by either system or third-party

Overview

This document defines the Content Screening API for Tizen platform. The API enables caller modules and applications to scan the content inside their logic data. The Content Screening API is defined in native C language. A computer language bundle might be required if calling from any other language. For example, if we want to call Content Screening API from Java, we need to add JNI code (language bundle) to enable Java code to call Content Screening API from virtual machine.




Figure 1 Overview of Content Screening

This document is to define the plug-in API specification in Tizen Security Interfaces for security vendor to implement the plug-in into Tizen OS.

The API is composed by following categories:

- Initialization and clean-up functions
- Scan functions
- Support functions




Figure 2 API Call Diagram

`TCSPLibraryOpen()` and `TCSPLibraryClose()` are used to initialize Tizen Content Screening library or clean up resource on application exit. `TCSPGetLastError()` is a support function to return caller an error code to indicate the latest error during this library function call.

`TCSPScanData()` is used to scan content in the memory while `TCSPScanFile()` and `TCSPScanFileEx()` is used to scan the content on permanent storages, like SD card.

`TCSPGetInfo()` and `TCSPGetVersion()` are used to get Meta Information and Version of framework/plugin respectively.

Library

The delivery of Tizen Content Screening plug-in API should be a .so library: libengine.so

Initialize Functions

Summary

Methods	
TCSLIB_HANDLE	TCSPLibraryOpen() Initialize Tizen Content Screening library.
void	TCSPLibraryClose(TCSLIB_HANDLE hLib) Close Tizen Content Screening library by releasing all resources it occupied.

Methods

```
TCSLIB_HANDLE TCSPLibraryOpen()
```

Initialize Tizen Content Screening library. For example, allocating memory for internal data use, loading signature database, etc.

Parameters

None.

Returns

An instance of Tizen Content Screening library context.

```
void TCSPLibraryClose(TCSLIB_HANDLE hLib)
```

Destroy Tizen Content Screening library instance. Release all resources it occupies.

Parameters

hLib

Tizen Content Screening library instance returned by TCSPLibraryOpen().

Returns

None.

Get Version Function

Summary

Methods

const char*	TCSPGetVersion(void)
	Returns the version info.

Methods

```
const char* TCSPGetVersion(void)
```

Returns the version info.

Parameters

None.

Returns

Version info.

Get Info Function

Summary

Methods

const char*	TCSPGetInfo(void)
	Returns the meta info.

Methods

```
const char* TCSPGetInfo(void)
```

Returns the meta info. It contains information about vendor, product, application id and other details specific to each vendor.

Parameters

None.

Returns

Meta info. The info is a well-formed XML string with character encoding in UTF-8.

Example of the meta info is :

```
<?xml version="1.0" encoding="UTF-8"?>
<Root>
  <Plug>
    <Version>3.2.1</Version>
    <VendorName>McAfee</VendorName>
    <ProductName>TPCS</ProductName>
    <AppId>q7097a278m</AppId>
  </Plug>
</Root>
```

Scan Functions

Summary

Methods	
int	<pre>TCSPScanData(TCSLIB_HANDLE hLib, TCSScanParam *pParam, TCSScanResult *pResult)</pre> <p>Scan content in memory.</p>
int	<pre>TCSPScanFile(TCSLIB_HANDLE hLib, char const *pszFileName, int iDataType, int iAction, int iCompressFlag, TCSScanResult *pResult)</pre> <p>Legacy API for scanning content in file system.</p>
int	<pre>TCSPScanFileEx(TCSLIB_HANDLE hLib, char const *pszFileName, int iDataType, int iAction, int iCompressFlag, void *pPrivate, int (*pfCallBack)(void *pPrivate, int iReason, void *pParam), TCSScanResult *pResult)</pre> <p>Scan content in file system.</p>

Methods

```
int TCSPScanData (TCSLIB_HANDLE hLib,
                 TCSScanParam *pParam,
                 TCSScanResult *pResult)
```

Scan content in memory. Caller need to pass callback functions in pParam so that scanner can read or write data back and forth. Scan result will be returned in a data structure pResult. The integer return value of this function call is just to indicate if this call is success or not. For any failure of this function call please use TCSPGetLastError() to get detail information.

Parameters

hLib	Tizen Content Screening library instance returned by TCSPLibraryOpen().
pParam	Memory address of data structure instance TCSScanParam, see detail at TCSScanParam .
pResult	Memory address of data structure instance TCSScanResult, see detail at TCSScanResult .

Returns

- 0 – on success.
- 1 – on failure

```
int TCSPScanFile (TCSLIB_HANDLE hLib,
                 char const *pszFileName,
                 int iDataType,
                 int iAction,
                 int iCompressFlag,
```

```

void *pPrivate,
int (*pfCallBack)(void *pPrivate,
                  int iReason,
                  void *pParam),
TCSScanResult *pResult)

```

Legacy API for scanning content on file system, keep it for backward compatible. It requires scanner instance, file path, data type the file could be, and type of action for malware. It will return detail scan result in data structure instance pResult. The integer return value of this function call indicates if the call is success or not. For any failure of this function call please use TCSPGetLastError() to get detail information.

Parameters

hLib	Tizen Content Screening library instance returned by TCSPLibraryOpen().
pszFileName	Path to the file.
iDataType	Data type of the file. It could be set to unknown type, which leaves the scanner to determine. But by specifying the data type, potentially can accelerate the scanning progress. For detail information please see Data Type .
iAction	Action type if malware detected. Please find detail at Action Type .
iCompressFlag	0 – decompression disabled, 1 – decompress enabled
pResult	Memory address of data structure instance TCSScanResult, see detail at TCSScanResult .

Returns

- 0 – on success.
- 1 – on failure

```

int TCSPScanFileEx (TCSLIB_HANDLE hLib,
                   char const *pszFileName,
                   int iDataType,
                   int iAction,
                   int iCompressFlag,
                   void *pPrivate,
                   int (*pfCallBack)(void *pPrivate,
                                     int iReason,
                                     void *pParam),
                   TCSScanResult *pResult)

```

Scan content on file system. It requires scanner instance, file path, data type the file could be, and type of action for malware. It will return detail scan result in data structure instance pResult. The integer return value of this function call indicates if the call is success or not. For any failure of this function call please use TCSPGetLastError() to get detail information.

Parameters

hLib	Tizen Content Screening library instance returned by TCSPLibraryOpen().
pszFileName	Path to the file.
iDataType	Data type of the file. It could be set to unknown type, which leaves the scanner to determine. But by specifying the data type, potentially can accelerate the scanning progress. For detail information please see Data Type .

iAction	Action type if malware detected. Please find detail at Action Type .
iCompressFlag	0 – decompression disabled, 1 – decompress enabled
pPrivate	Caller context data. Instead performing direct access to this field, scanner will pass this context data back to caller via below callbacks, so that caller can track the access status inside their own context data without creating global variables.
pfCallBack	It is used by scanner to notify caller for specific events via this callback function. Return 0 to proceed scan and -1 to cancel the scan.
pResult	Memory address of data structure instance TCSScanResult, see detail at TCSScanResult .

Returns

- 0 – on success.
- 1 – on failure

Support Function

Summary

Methods	
int	TCSPGetLastError (TCSLIB_HANDLE hLib)
	Return last error code.

Methods

```
int TCSPGetLastError (TCSLIB_HANDLE hLib)
```

This function is used to retrieve the error code previous function call occurs. All scan functions return zero to indicate success, and -1 for failure. The error code gives the detail of the failure reason for trouble shooting.

Parameters

hLib	Tizen Content Screening library instance returned by TCSPLibraryOpen().
------	---

Returns

Error code, please find detail at [Error Code](#).

TCSScanParam

Description

Data structure for caller to pass input data for scanning.

Summary

Fields	
iAction	The type of action that caller want to take when malware detected. Please find detail at Action Type .
iDataType	The type of content data. For example, archived file. Please find detail at Data Type .
iCompressFlag	0 – decompression disabled, 1 – decompression enabled.
pPrivate	Caller context data. Instead performing direct access to this field, scanner will pass this context data back to caller via below callbacks, so that caller can track the access status inside their own context data without creating global variables.
unsigned int	(*pfGetSize) (void *pPrivate) It is used by scanner to obtain content data size in bytes from caller via this callback function.
int	(*pfSetSize) (void *pPrivate, unsigned int uSize) It is used by scanner to change content data size in bytes via this callback function. (For example, repair infected data)
unsigned int	(*pfRead) (void *pPrivate, unsigned int uOffset, void *pBuffer, unsigned int uCount) It is used by scanner to read content data in bytes from caller via this callback function.
unsigned int	(*pfGetWrite) (void *pPrivate, unsigned int uOffset, void const *pBuffer, unsigned int uCount) It is used by scanner to change content data in bytes via this callback function.
int	(*pfCallBack) (void *pPrivate, int iReason, void *pParam) It is used by scanner to notify caller for specific events via this callback function.

Callback methods

```
unsigned int (*pfGetSize) (void *pPrivate)
```

To scan content data in memory, scanner needs to know the size of the data to be scanned. This callback function is supposed to return the content data size in bytes to scanner.

Parameters

pPrivate Caller context data.

Returns

Size in bytes.

```
int (*pfSetSize) (void *pPrivate, unsigned int uSize)
```

When scanner try to repair destroyed content data by malware, it usually needs to change the size of content data size, so that caller can do coordinate work for this change.

Parameters

pPrivate	Caller context data.
uSize	New size in bytes

Returns

Size in bytes, not equal to expected size indicating failure of this call.

```
unsigned int (*pfRead) (void *pPrivate,  
                        unsigned int uOffset,  
                        void const *pBuffer,  
                        unsigned int uCount)
```

When scanner scan the content data in memory it needs to read data from caller instead of directly access the memory, this enables flexibility for scanner to handle variable format of content data and stream scanning.

Parameters

pPrivate	Caller context data.
uOffset	Offset where to start reading
pBuffer	The memory address of buffer which is to be filled with read data as result of this read call.
uCount	Bytes to be read

Returns

Read bytes count, not equal to expected size indicating failure of this call.

```
unsigned int (*pfWrite) (void *pPrivate,  
                        unsigned int uOffset,  
                        void const *pBuffer,  
                        unsigned int uCount)
```

When scanner repair the broken content data in memory it needs to write data through this callback.

Parameters

pPrivate	Caller context data.
uOffset	Offset where to start writing
pBuffer	The memory address of buffer which is to be copied to the specified offset.
uCount	Bytes to be written

Returns

Written bytes count, not equal to expected size indicating failure of this call.

```
int (*pfCallBack) (void *pPrivate,  
                  int iReason,  
                  void *pParam)
```

When scanner repair the broken content data in memory it needs to write data through this callback.

Parameters

pPrivate	Caller context data.
iReason	Reason for scanner to call caller. Please find detail

pParam at [Callback Reason](#).
Coordinate parameter for specific reason. Please
find detail at [Callback Reason](#).

Returns

0 – indicating success
Negative value – indicating stop scanning

TCSScanResult

Description

Data structure for scanner to pass detail scan result back to caller.

Summary

Fields	
iNumDetected	The number of detections.
pDList	Detection list, please find detail at TCSDetected .
void	(*pfFreeResult) (struct TCSScanResult_struct *pResult) It is used by caller to release detection list resources when needed.

Callback methods

```
void (*pfFreeResult) (struct TCSScanResult_struct *pResult)
```

Caller has to pass scan result instance back to this callback function to release resources used by detection list.

Parameters

pResult The scan result instance.

Returns

None.

TCSDetected

Description

Data structure for scanner to pass detection information to caller.

Summary

Fields	
pNext	Detection structure is a link list node.
pszName	Malware name.
pszVariant	Malware variant name.
uType	Malware type. Please see below table for detail.
uAction	Bit-field of malware severity, class and behaviour level. Please find detail in below table.
pszFileName	Path of the infected file, it can be ignored if current is a memory data scan.

TCS_DTYPE_URL	Content data is URL.
TCS_DTYPE_EMAIL	Content data is e-mail.
TCS_DTYPE_PHONE	Content data is phone number.
TCS_DTYPE_JAVA	Content data is Java code.
TCS_DTYPE_JAVAS	Content data is JavaScript.
TCS_DTYPE_TEXT	Content data is plain text.

Action Type

Description

Action type that caller want to take on detected malware.

Summary

Fields	
TCS_SA_SCANONLY	Tell scanner scan content data without changing anything.
TCS_SA_SCANREPAIR	Tell scanner to repair content data if detected.

Callback Reason

Description

Reason codes for scanner to callback on caller.

Summary

Fields	
TCS_CB_DETECTED	Tell caller that malware was detected.

The coordinate parameter for this callback reason is [TCSDetected](#)

Error Code

Description

Error code definition is a bit-field.



Component code

Fields

TCS_ERROR_MODULE_GENERIC	Generic error can be occurred in all components.
--------------------------	--

Error code

Fields

TCS_ERROR_NOT_IMPLEMENTED	Tizen Content Screening library is not implemented.
---------------------------	---

Call Sequence

