

NAME

CURLOPT_HTTPGET – ask for a HTTP GET request

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_HTTPGET, long useget);
```

DESCRIPTION

Pass a long. If *useget* is 1, this forces the HTTP request to get back to using GET. Usable if a POST, HEAD, PUT, etc has been used previously using the same curl *handle*.

When setting *CURLOPT_HTTPGET(3)* to 1, it will automatically set *CURLOPT_NOBODY(3)* to 0 and *CURLOPT_UPLOAD(3)* to 0.

DEFAULT

0

PROTOCOLS

HTTP(S)

EXAMPLE

```
curl = curl_easy_init();
if(curl) {
    curl_easy_setopt(curl, CURLOPT_URL, "http://example.com");

    /* use a GET to fetch this */
    curl_easy_setopt(curl, CURLOPT_HTTPGET, 1L);

    /* Perform the request */
    curl_easy_perform(curl);
}
```

AVAILABILITY

Along with HTTP

RETURN VALUE

Returns CURLE_OK if HTTP is supported, and CURLE_UNKNOWN_OPTION if not.

SEE ALSO

CURLOPT_NOBODY(3), **CURLOPT_UPLOAD(3)**,